



PRODUCT DATA SHEET

HF4R Work (C90)



HF4R Work

PRODUCT DESCRIPTION

The Ledlenser HF4R Work is our slim and lightweight basic model for industry and trade. In addition to three brightness levels and a red front light, the HF4R Work is equipped with a high color rendering index for close-range work. The steplessly tilting lamp head provides flexibility. Protective elements at the front prepare the lamp for demanding applications – thanks to its efficient battery, you can use the HF4R Work for up to eight hours at mid-intensity. You can easily charge the integrated battery via Magnetic Charge System. Other clever features include the handy transportation lock as well as various mounting options on helmets.

- Slim headlamp with three brightness levels as well as red front light
- Bright and perfectly balanced light pattern; two light sources for short and long-range illumination
- Protective elements at the front for high impact resistance; suitable for continuous immersion in water (IP68)
- Efficient battery; easily rechargeable via Magnetic Charge System, with battery status indicator
- Mounting option on helmet via rubberized headband or enclosed helmet mount and adapter

TECHNICAL DATA

Weight incl. batteries [g]	79
Focus function	No
Head material	PC
Tube material	PC
Optic	Plastic lense (PMMA)
Headband material	Elastic fabric
Headband type	Side headband
Head movement type	Stepless movement
Head movement angle [°]	45
Headband specifications	Detachable, Elastic, Rubberised back, Washable

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	No
Total battery voltage [V]	3.7
Total battery capacity [mAh]	1000
Total battery energy ² [Wh]	3.7
Rechargeable	Yes
Charging time ⁵ [min]	180
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

IP class	IP68
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Boost, Power, Mid Power, Low Power

LIGHT SOURCE

Amount LEDs	2
LED type	High Power LED
Color	White
Color temperature [K]	4600 to 5400
Color rendering index (CRI)	80

LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	500	300	80	20
Beam distance ¹ [m]	130	100	60	15
Run time ¹ [h]		2.5	8	35

SWITCH

Front Switch

FEATURES

Red Light, Transportation lock, Memory Function, Backup Mode

TECHNOLOGIES

Temperature Control System, Magnetic Charge System, Fusion Beam

HF4R Work

ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME
Fastenings / Brackets	503002	Wall Mount Type C
Fastenings / Brackets	502256	Universal Mounting Bracket Type E
Fastenings / Brackets	502314	Helmet Connecting Kit Type H
Fastenings / Brackets	502254	Helmet Mount for Euroslot Type A
Pouches / Holster	0332	Pouch Type H
Charger / Cable	502265	Magnetic Charging Cable Type A
Charger / Cable	502929	USB-C Adapter 20W