

PRODUCT DATA SHEET P18R Work (C56)







P18R Work

PRODUCT DESCRIPTION

The P18R Work is the lumen flagship of the Work-series. Thanks to the X-Lens Technology and an incredi le 4500 lumens, the flashlight ensures that darkness never makes for unfinished work. The Ledlenser patented Advanced Focus System provides precise spot or flood lighting with up to 720 meters range. Our forward-thinking Smart Light Technology allows the selection of personalised light functions and sequences. The powerful Eattery of the P18R Work is quickly charged with the practical Magnetic Charge System.

- Extremely powerful: 4500-lumens-flashlight in a compact and robust housing
- Flicker-free, constant light provides perfect illumination for fast moving parts and machines
- Rubber covers on the lamp head and end cap protect against impact and offer increased grip; lens shield protects the lens from impact and dirt
- Customizable light functions thanks to Smart Light Technology
- Advanced Focus System for efficient, precise flood and spot lighting

| TECHNICAL DATA | | |
|------------------------------|----------------------|--|
| Length defocused [mm] | 183 | |
| Length focused [mm] | 190 | |
| Head diameter [mm] | 99 | |
| Tube diameter [mm] | 47 | |
| Weight incl. batteries [g] | 669 | |
| Weight without batteries [g] | 501 | |
| Focus function | Yes | |
| Head material | Aluminum alloy | |
| Tube material | Aluminum alloy | |
| Optic | Plastic lense (PMMA) | |
| Cartridge | No | |

POWER SUPPL Rechargeable battery Power source type Battery quantity 1 Li-ion Battery type Total battery voltage [V] 11.1 3000 Total battery capacity [mAh] Total battery energy [Wh] 33.3 Rechargeable Yes 330 Charging time [min] Energy modes **Constant Light** Energy status indicator Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

| IP class | IP54 |
|--------------------------------|------------|
| Drop test (drop height) [m] | 1 |
| Working temperature range [°C] | -20 to +40 |

LIGHT FUNCTIONS

Blink, Boost, Low Power, Mid Power, Power, Position, S.O.S., Strobe

| LIGHT SOURCE | |
|-----------------------------|--------------|
| Amount LEDs | 3 |
| LED type | Xtreme LED |
| Color | White |
| Color temperature [K] | 4700 to 5500 |
| Color rendering index (CRI) | 70 |
| | |

| LIGHT VALUES | | | | | |
|-----------------------|-------|-------|-----------|-----------|--|
| ANSI – Constant Light | Boost | Power | Mid Power | Low Power | |
| Light output [lm] | 4500 | 2600 | 1000 | 30 | |
| Beam distance [m] | 720 | 420 | 260 | 50 | |
| Run time [h] | | 2.5 | 4.5 | 70 | |

SWITCH

Front Switch

FEATURES

Transportation lock , Dimmable , Flicker Free, Memory Function, Back-Up Light

TECHNOLOGIES

Advanced Focus System, Emergency Light, Rapid Focus, Smart Light Technology, Temperature Control System, Magnetic Charge System, X-Lens Technology



—P18R Work

ACCESORIES

| PRODUCT CATEGORY | ITEM NUMBER | PRODUCT NAME | |
|----------------------------|-------------|--------------------------------|--|
| Color filter / Signal caps | 501507 | Color Filter Blue 85.5mm | |
| Color filter / Signal caps | 501508 | Color Filter Red 85.5mm | |
| Color filter / Signal caps | 501509 | Color Filter Green 85.5mm | |
| Color filter / Signal caps | 501510 | Color Filter Yellow 85.5mm | |
| Roll Protections | 502242 | Roll Protection 85.5mm | |
| Charger / Cable | 502265 | Magnetic Charging Cable Type A | |
| Charger / Cable | 0380 | USB Car Charger | |
| Charger / Cable | 502271 | USB Adapter 2.4A | |

